


DURACELL® Rechargeable



Value Charger CEF14 (Wally)



DESIGN

International Charge Capability – device can be used worldwide (with suitable AC converter plug)

- Primary plug matches local requirements
- New attractive compact and modern design

BENEFITS

- Great Value!
- New sleek & compact design
- Simple and Easy to Use with Convenient Wall Plug-In

FEATURES

Charges Both AA & AAA NiMH Cells
Comes with 4x AA Duracell 1800mAh
Charges in Six Hours*
LED Indicator

- Red = Charging
 - Green = Complete or trickle charge
 - Flashing Red = Error – Abnormal battery or temperature
- Maintenance Charge Keeps Cells Fresh

SAFETY

Microprocessor Controlled

- Charge Termination based on dV and built-in timer
- Primary Cell Detection – will not charge non-rechargeable batteries
- Reverse Polarity Protection
- Over-temperature shut-off – prevents overheat of cell
- Over-charge protection – prevents cell damage

TECHNICAL

Battery Charger	Class 2, Integral Power Supply
Plug	Direct Plug-In Matches Local Requirements
Battery Type	NiMH HR6/AA or HR03/AAA
Battery Fit	2 or 4 NiMH AA/HR6, 2 NiMH AAA/HR03
Product Weight	207 grams
Input	100–240V AC, 50–60 Hz
Output	HR6/AA: 5.6V DC 0.36A, HR03/AAA: 2.8V DC 0.16A
Operating Temperature	0° C – 35° C (32° F – 95° F)
Product Dimensions	217mm (H) x 102mm (W) x 72mm (D)

*Charge rate and time is dependent on cell capacity, discharge state, and operating temperature.

